

# 2700954

tarmac rally - race

Hyundai 160hp / 230Nm

V-6cyl 2.5L 24v DOHC (DTH/DTH)



**intake**                      **exhaust**

**camshaft data:**


lash ramp	: 0.25mm	0.25mm
duration @ 0.1mm	: 277°	269°
duration @ 1.0mm	: 243°	236°
valve lift	: 12.00mm	11.50mm
cam lift	:	:
lobe angle	: 106°	106°
timing @ 1.0mm	: 16° / 47°	44° / 12°
valve lift @ TDC	: 3.20mm	2.65mm

**parts setup:**

cam wheels :	:	:
follower	:  CC017	:  CC017
valve lash	:  TS101	:  TS101
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: O.E.M.	: O.E.M.
lower retainer	: O.E.M.	: O.E.M.
exterior spring	:  PAC-E99862	:  PAC-E99862
interior spring	:	:

fitted load / length	: 31kg @ 34.5mm	: 33kg @ 34.0mm
max. load / lift	: 85kg @ 12.5mm	: 85kg @ 12.0mm

**REMARKS :**



**REMARKS :**

- # - valve clearance is to be adjusted using mechanical lash caps
- please make sure that the lash cap does not touch the valve locks !
- # FOR COMPETITION APPLICATIONS ONLY. Following details must be verified:
  - the camshafts must turn smooth in the cylinderhead, provide free travel by machining where needed
  - distance between valve seal and retainer at full lift must be 0.6mm at least
  - minimum valve spring travel of 1.0mm at full lift must be provided
  - distance between valve and piston 1.0mm (pref. 1.5mm). check 5-15° before TDC on exhaust, and after TDC on intake
- # ONLY for use in competition engines with independent engine management (throttle position sensor) or carburettors