

2340878

tarmac rally - race


Ford YBB Cosworth 4WD

I-4cyl 2.0L 16v DOHC (DTH/DTH)



	intake	exhaust
camshaft data:		
lash ramp	: 0.25mm	0.25mm
duration @ 0.1mm	: 305°	301°
duration @ 1.0mm	: 262°	254°
valve lift	: 13.00mm	12.50mm
cam lift	:	
lobe angle	: 105°	105°
timing @ 1.0mm	: 26° / 56°	52° / 22°
valve lift @ TDC	: 4.55mm	4.05mm
parts setup:		
cam wheels :	: CSK5119	: CSK5119
follower	: CC005	: CC005
valve lash	: TS102	: TS102
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: 99366	: 99366
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: PAC-E12009	: PAC-E12009
interior spring	: PAC-I12009	: PAC-I12009
fitted load / length	: 38kg @ 33.0mm	: 38kg @ 33.0mm
max. load / lift	: 108kg @ 14.0mm	: 108kg @ 14.0mm

REMARKS :



REMARKS :

- # camshafts for atmospheric (naturally aspirated) engines
- # FOR COMPETITION APPLICATIONS ONLY. Following details must be verified:
 - the camshafts must turn smooth in the cylinderhead, provide free travel by machining where needed
 - distance between valve seal and retainer at full lift must be 0.6mm at least
 - minimum valve spring travel of 1.0mm at full lift must be provided
 - distance between valve and piston 1.0mm (pref. 1.5mm). check 5-15° before TDC on exhaust, and after TDC on intake
- # - valve clearance is to be adjusted using mechanical lash caps
- please make sure that the lash cap does not touch the valve locks !
- # ONLY for use in competition engines with independent engine management (throttle position sensor) or carburetors