

4901902

tarmac rally - race

Citroën EW10J4S 180hp

I-4cyl 2.0L 16v DOHC (DTH/DTH)



	intake	exhaust
camshaft data:		
lash ramp	: 0.25mm	0.25mm
duration @ 0.1mm	: 285°	274°
duration @ 1.0mm	: 251°	240°
valve lift	: 12.50mm	11.75mm
cam lift	:	
lobe angle	: 104°	108°
timing @ 1.0mm	: 22° / 49°	48° / 12°
valve lift @ TDC	: 3.95mm	2.65mm


parts setup:

cam wheels :	:	:
follower	: CC017	: CC017
valve lash	: TS101	: TS101
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: 99410/s	: 99410/s
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: PAC-S90015	: PAC-S90015
interior spring	:	:

fitted load / length	: 30kg @ 38.0mm	: 30kg @ 38.0mm
max. load / lift	: 79kg @ 13.0mm	: 79kg @ 13.0mm

REMARKS :

- #
- # Inlet Valves: #
- 9249003 d6.00 // D35.0 // L106.1 #
- Exhaust Valves: #
- 9249004 d6.00 // D31.0 // L102.9 #



REMARKS :

- # Camshafts for use with original VVT system (intake only)
- # FOR COMPETITION APPLICATIONS ONLY. Following details must be verified:
 - the camshafts must turn smooth in the cylinderhead, provide free travel by machining where needed
 - distance between valve seal and retainer at full lift must be 0.6mm at least
 - minimum valve spring travel of 1.0mm at full lift must be provided
 - distance between valve and piston 1.0mm (pref. 1.5mm). check 5-15° before TDC on exhaust, and after TDC on intake
- # - valve clearance is to be adjusted using mechanical lash caps
- # - please make sure that the lash cap does not touch the valve locks !
- # disable VANOS system
- # ONLY for use in competition engines with independent engine management (throttle position sensor) or carburettors