

6700604

hot street - dirt track


Suzuki G13B 100hp

I-4cyl 1.3L 16v DOHC (DTH/DTH)



	intake	exhaust
camshaft data:		
lash ramp	: hydro	hydro
duration @ 0.1mm	: 271°	261°
duration @ 1.0mm	: 225°	218°
valve lift	: 10.00mm	9.00mm
cam lift	:	
lobe angle	: 108°	108°
timing @ 1.0mm	: 4° / 41°	37° / 1°
valve lift @ TDC	: 1.50mm	1.10mm
parts setup:		
cam wheels :	:	:
follower	: O.E.M.	: O.E.M.
valve lash	: O.E.M.	: O.E.M.
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: O.E.M.	: O.E.M.
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: O.E.M.	: O.E.M.
interior spring	:	:
fitted load / length	: 33kg @ 42.0mm	: 33kg @ 42.0mm
max. load / lift	: 80kg @ 10.0mm	: 80kg @ 10.0mm

REMARKS :



REMARKS :

- # - steel billet camshafts
- please carefully read about the different valve spring options
- # ONLY for dirt track applications and pro street use with adjustable engine management or carburetors